



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X Rust

PRODUCT CODE – VCI Jelly Wax Based 164

PRODUCT DESCRIPTION

RUST-X VCI Jelly Wax 164 is a viscous wax type mineral oil based product, which can be applied with a brush. The viscous gel hardens to form a waxy coat which is highly active against corrosion under the most damaging environmental conditions and provides long-term corrosion protection to the parts on which it is applied.

The VCI Jelly Wax is tacky and stays on the surface and is not easily removed by handling and re-handling. This can be used to protect structures, chemical plants and equipment that are intended for outdoor storage or are located in open areas and need protection. These can also be used to protection unpacked refinery equipment oil pipeline equipment and valves, off shore refinery parts which are not painted or coated and require protection or during the storage while commissioning, for lay-up during shut-downs and also on heat exchangers, windmills and auto motives.

This can also be used to protect Defense Equipment and installations where extreme climatic conditions may have detrimental effect on the properties of the equipment e.g. on cannons, guns, artillery, launch vehicles

etc. It can be applied on machined surfaces of automotive equipment such as Transmissions, Gear Boxes, Engine Blocks, Flywheels, Hydraulic Pistons or other machined and unpainted surfaces to keep them from corrosion during storage and transportation.

All RUST-X rust preventive oils are Barium & Heavy Metal Free.

FEATURES

- Easy to use by brush or hand application.
- Transparent upon application
- Liquid displaceable film, which does not dry and hence does not cause physical change in part dimensions.
- Protects parts for upto 5 years in packed condition in open areas and upto 10 years indoors
- Highly hydrophobic and water displacing
- High Alkalinity Reserve
- Self-healing & self-lubricating
- Does not affect paint or coatings
- Can also be used in threaded areas and prevents water penetration and thread locking
- Compatible with Engine and Transmission Lubricants and need not be removed during assembly



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X Rust

PRODUCT CODE – VCI Jelly Wax Based 164

- Environment Friendly

APPLICATIONS

- This can be used to protect structures, chemical plants and equipment that are intended for outdoor storage located in open areas and need protection.
- These can also be used to protection unpacked refinery equipment oil pipeline equipment and valves, off shore refinery parts which are not painted or coated and require protection or during the storage while commissioning, for lay-up during shut downs and also on heat exchangers, windmills and automotive.
- Can be used on the chemical plant and equipment which operates at elevated temperatures.
- This can also be used to protect Defense Equipment and installations
- It can be applied on machined surfaces of automotive equipment.

USAGE

Clean the area to be protected using a cloth or RUST-X 40 spray. Apply the RUST-X wax with a brush on the area to be protected. Ensure that all the area gets covered evenly with the wax. VCI Wax 164 can be applied by dipping, brushing or spraying.

PACKAGING AND STORAGE

Store in a cool dry place and always keep RPO sealed when not in use.

TECHNICAL SPECIFICATION

Physical Properties	Test Method	Value
Color	Visual	Amber Liquid
Freezing Point		-20°C
Specific Gravity	ASTM D 1298	0.87
Film Thickness (Depends upon application method)		25-200 microns
Appearance		Waxy
Flash Point	ASTM D 92	105°F
Degreasability with solvents		Passes
Indoor Protection Life in VCI packaging		10 Years
Outdoor Protection Life in VCI packaging		5 Years
Outdoor Protection Life Open (covered)		2 -3 Years
Salt Spray Test		1000hrs
Coverage (Depends upon application method brush or dip)		Upto 3-5sq meters/ltr
Humidity cabinets	ASTM-D-1748	1500 hours
Indoor Protection Life (open)		6 months+
Indoor protection life (packed)		2 years+
Packaged Protection Life (In VCI Packaging)		Up to 5 Years



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X Rust

PRODUCT CODE – VCI Jelly Wax Based 164

APPLICATION PICTURES



DISPOSAL

Recommendation: Do not allow product to reach sewage system.

Disposal of product or waste must comply with official local regulations.

Packaging that cannot be recycled must be disposed in

the same manner as the product.

HEAVY METALS DECLARATION

RUST-X Rust Preventive products do not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated di-phenylether complying with the restricted substances listed in Article 4(1) of the RoHS Directive. RUST-X Rust Preventive Oils are also REACH Compliant for exports to the European Union.

SAFETY INFORMATION

- Keep Out Of Reach Of Children
 - Keep Container Tightly Closed
 - Not For Internal Consumption
 - Consult Material Safety Data Sheet For More Information
 - Safe for people
 - This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.
 - Rust-X VCI chemistry is safe for sensitive electronics.
 - Rust-X VCI chemistry imposes No galvanic effects, residues or changes in the properties of metals.
- The protective molecules dissipate upon opening of package.

DECLARATION

This Data sheet and information it contains is considered to



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X Rust

PRODUCT CODE – VCI Jelly Wax Based 164

be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations.

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on validations and tests conducted by HI TECH INTERNATIONAL/RUST-X or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Rust-X, Hi Tech International or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the film sold.

Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied

warranty of merchantability or of fitness for a particular purpose. In no case shall HI TECH INTERNATIONAL/RUST-X be liable for incidental or consequential damages.

GLOBAL SUPPORT

Algeria Angola Argentina Australia Austria Bangladesh Belarus Belgium Bhutan Bolivia Brazil Canada Chile China Colombia Czech Republic Democratic Republic of the Congo Denmark Ecuador Estonia Finland France Gabon Germany Hungary India Indonesia Ireland Italy Japan Kazakhstan Korea Latvia Lithuania Luxembourg Malaysia Mexico Monaco Morocco Nepal Netherlands Nigeria Norway Peru Philippines Poland Portugal Republic of Congo Romania Russia Singapore Slovak Republic Slovenia South Africa Spain Sri Lanka Sweden Switzerland Taiwan Thailand Tunisia Turkey Ukraine United Arab Emirates and MENA (Middle East & North Africa) United Kingdom United States Uruguay Vietnam

DISTRIBUTOR

FOR INDUSTRIAL USE ONLY

Revision No. 1 Revision Date: 1st March 2018