



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X RP Oil

PRODUCT CODE – RUST-X 1130 AFR

PRODUCT DESCRIPTION

The Heavy Duty grade as the name implies provides long term corrosion protection against the most damaging environmental conditions and provides excellent acid fume resistance.

The protection of this oil surpasses the capability of any generic rust preventive and provides excellent protection even in open environments, sea worthy protection during exports as well as during long term storages of the components.

This Heavy Duty oil forms a light coat of rust preventive layer on the component which is not easily removable with light abrasive forces during handling, transportation and storages in protected or un-protected conditions.

This grade provides multi-purpose degreasing, dewatering and corrosion protection to the component on application. The grade is removable by washing with solvents or water based cleaners.

The product has a high flash point and can be used for protection of Cold Rolled Steel, Engine Components, as well as large

equipment where indoor open storages are required. All RUST-X rust preventive oils are Barium & Heavy Metal Free.

FEATURES

- VCI Properties
- Acid fume resistance with high alkaline reserve
- Fine film with strong adherence to the surface. High Flashpoint solvent for safety & lower evaporation loss.
- Dries to form a non-stick & dry feel film after 60-90 minutes of application.
- Excellent protection against acidic and saline environments
- Excellent Dewatering & Degreasing Properties
- Protective Film that does not get scratched easily and protects during handling and outdoor storage.

APPLICATIONS

- Cast Iron components
- Forgings
- Machined components
- Chemical Plants & Equipments
- Oil Rig Equipment
- Heavy Components
- Wind mill components & components that have to be stored/used in open or in acidic environments



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X RP Oil

PRODUCT CODE – RUST-X 1130 AFR

TECHNICAL SPECIFICATION

Physical Properties	Test Method	Value
Colour	Visual	Amber Clear
Viscosity @ cSt @ 40°C	ASTM D 445	16-20 cst
Specific Gravity	ASTM D 1298	0.78 - 0.86
Flash Point (before application)	ASTM D 92	130 °C
Flash Point (after application)	ASTM D 92	<220°C
Volatiles by % (by weight)		15 %
Coverage (sq m/ Lt)		80-100
Film thickness	IS 2074	2-4 microns
Pour Point	ASTM D 97	Below -6°C
Saponification Value (mg KOH/gm)	ASTM D 94	5.0-7.0
Salt Spray Protection	ASTM B 117	36-48 hours
Salth Spray in VCI Packaging	ASTM D 1748	720 hours +
Condensation Test		> 60 cycles
Humidity Chamber		720 hours +
Indoor Protection Life (open)		2-3 months
Indoor protection life (packed)		2 years
Packaged Protection Life (In VCI Packaging)		Upto 5 Years

PACKAGING AND STORAGE

Store in a cool dry place and always keep RPO sealed when not in use.

USAGE

Dipping by far is the best method for establishing an even layer on the component. Other methods may be used such as mist spraying, electrostatic spraying, brushing, automatic conveyor spray or dip process pray. It is important that the complete surface of the component is coated with the rust preventive oil.

Use of gloves while handling the components as well as immediate packaging is important. In case the components carry cutting oils or water from previous processes, dewatering with CL005 is recommended.

DISPOSAL

Recommendation: Do not allow product to reach sewage system.

Disposal of product or waste must comply with official local regulations.

Packaging that cannot be recycled must be disposed in the same manner as the product.



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X RP Oil

PRODUCT CODE – RUST-X 1130 AFR

APPLICATION PICTURES



Polybrominated di-phenylether complying with the restricted substances listed in Article 4(1) of the RoHS Directive. RUST-X Rust Preventive Oils are also REACH Compliant for exports to the European Union.

SAFETY INFORMATION

- Keep Out Of Reach Of Children
- Keep Container Tightly Closed
- Not For Internal Consumption
- Consult Material Safety Data Sheet For More Information
- Safe for people
- This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.
- Rust-X VCI chemistry is safe for sensitive electronics.
- Rust-X VCI chemistry imposes No galvanic effects, residues or changes in the properties of metals. The protective molecules dissipate upon opening of package.

DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations.

HEAVY METALS DECLARATION

RUST-X Rust Preventive products do not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or

LIMITED WARRANTY

All statements, technical information and

USA - 14310 Gannet St , La Mirada, California
info@rustxusa.com www.rustxusa.com
Italy | France | India | China | Mexico





TECHNICAL DATASHEET

PRODUCT NAME – RUST-X RP Oil

PRODUCT CODE – RUST-X 1130 AFR

recommendations contained herein are based on validations and tests conducted by HI TECH INTERNATIONAL/RUST-X or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Rust-X, Hi Tech International or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the film sold.

Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In no case shall HI TECH

INTERNATIONAL/RUST-X be liable for incidental or consequential damages.

GLOBAL SUPPORT

Algeria Angola Argentina Australia Austria Bangladesh Belarus Belgium Bhutan Bolivia Brazil Canada Chile China Colombia Czech Republic Democratic Republic of the Congo Denmark Ecuador Estonia Finland France Gabon Germany Hungary India Indonesia Ireland Italy Japan Kazakhstan Korea Latvia Lithuania Luxembourg Malaysia Mexico Monaco Morocco Nepal Netherlands Nigeria Norway Peru Philippines Poland Portugal Republic of Congo Romania Russia Singapore Slovak Republic Slovenia South Africa Spain Sri Lanka Sweden Switzerland Taiwan Thailand Tunisia Turkey Ukraine United Arab Emirates and MENA (Middle East & North Africa) United Kingdom United States Uruguay Vietnam

DISTRIBUTOR

FOR INDUSTRIAL USE ONLY

Revision No. 1 Revision Date: May 2019